

Power Team

	Page
HOSES	122
Rubber	
Polyurethane	
Non-Conducting	
	Page
COUPLERS	123
Quick Connect	
Flush Face	
	Page
GAUGES	124-125
Heavy Duty Hydraulic Pressure Gauges	
Digital and Analog	
	Page
FLUIDS	126
Standard Oil 0,9 I, 3,8 I, 9,5 I, 208	31
Flame Out 3,8 I, 9,5 I	
Bio Degradable 3,8 I, 9,5 I	
Low Temperature 3,8	
	Parto
MANIFOLDS	127 *
Standard Blocks	
Blocks with Valves	
700 BAR FITTINGS	Page 128
Connectors	
Couplings	
Crosses	A Comment
Elbows	
Tees	
Swivels	
Special Adapters	
	Page
VALVES	129-133 🐨
In-Line	
Remote	
See Also Pump Mountedpages 45-51	States and a little

121

Hoses

A C C E S S O R L E S

וועטוגעטונפ

Polyurethane Rubber Non-Conductive

• 3/8" NPTF fittings on both ends. • Operating pressure is 700 bar. All comply with SAE 100R10 standard.

A Non-conductive hose

For applications requiring electrical isolation by the hose, non-conductive hose has a leakage factor of less than 50 microamperes, considered a safe level of conductivity by SAE standards. The covering is polyurethane and colored orange for easy identification as non-conductive hose. The covering is not perforated, preventing moisture from entering the hose and affecting its overall conductivity. All non-conductive hoses have a minimum burst pressure of 2.800 bar.

B Rubber hose

6 spiral (R13 specification) rated hose reinforced with two braids of high tensile steel wire and have a tool 4:1 safety factor. The rubber covering is oil and weather resistant.



The figures show the relative effect two styles of hose can have on return time. Actual times may vary.

	CYLINDER RETURN	TIME
	No. 9769E 3,1 m Hose	No. 9781E 3,1 m Hose
Cylinder	6,4 mm I.D.	9,5 mm I.D
C2514C	51 sec.	14 sec.
C556C	1 min., 30 sec.	24 sec.
C5513C	4 min., 12 sec.	59 sec.
C10010C	6 min., 56 sec.	1 min., 3 sec.

G

cap.

2800 bar BP.

Polyurethane hose

Made with Nylon core and then one braid of

Aramid and one braid of wire reinforcement

4:1 safety factor standard 700 bar WP /

No. 9764E - Hose assembly consisting of

9767E (1,8 m hose), 6,4mm I.D. polyurethane

No. 9754 - Hose assembly consisting of 9756

with 9798 hose half coupler and 9800 dust

(1,8 m hose), 6,4 mm I.D. rubber with 9798

hose half coupler and 9800 dust cap.

Hydraulic hose assembly

with a orange polyurethane cover (Conductive).

				ORDERING IN	FORMATION				
		Hose	Burst	Order			Hose	Burst	Order
Hose Type	Hose I.D.	Length	Rating	No.	Hose Type	Hose I.D.	Length	Rating	No.
Polyurethane	6,4 mm	0,6 m	2 800 bar	9765E	Rubber, Wire-braid	6,4 mm	2,4 m	2 800 bar	9757E
Polyurethane	6,4 mm	0,9 m	2 800 bar	9766E	Rubber, Wire-braid	6,4 mm	3,1 m	2 800 bar	9758E
Polyurethane	6,4 mm	1,8 m	2 800 bar	9767E	Rubber, Wire-braid	6,4 mm	3,7 m	2 800 bar	9759E
Polyurethane	6,4 mm	1,8 m	2 800 bar	9764E [*]	Rubber, Wire-braid	6,4 mm	6,1 m	2 800 bar	9760E
Polyurethane	6,4 mm	2,4 m	2 800 bar	9768E	Rubber, Wire-braid	6,4 mm	9,1 m	2 800 bar	9761E
Polyurethane	6,4 mm	3,1 m	2 800 bar	9769E	Rubber, Wire-braid	6,4 mm	15,3 m	2 800 bar	9762E
Polyurethane	6,4 mm	3,7 m	2 800 bar	9770E	Rubber, Wire-braid	9,5 mm High Flow	0,9 m	2 800 bar	9733E
Polyurethane	6,4 mm	6,1 m	2 800 bar	9771E	Rubber, Wire-braid	9,5 mm High Flow	1,8 m	2 800 bar	9776E
Polyurethane	6,4 mm	15,3 m	2 800 bar	9772E	Rubber, Wire-braid	9,5 mm High Flow	3,1 m	2 800 bar	9777E
Polyurethane	6,4 mm	22,9 m	2 800 bar	9750E	Rubber, Wire-braid	9,5 mm High Flow	4,6 m	2 800 bar	9734E
Polyurethane	6,4 mm	30,5	2 800 bar	9751E	Rubber, Wire-braid	9,5 mm High Flow	6,1 m	2 800 bar	9778E
Polyurethane	9,5 mm High Flow	1,8 m	2 800 bar	9780E	Rubber, Wire-braid	9,5 mm High Flow	9,1 m	2 800 bar	9735E
Polyurethane	9,5 mm High Flow	3,1 m	2 800 bar	9781E	Rubber, Wire-braid	9,5 mm High Flow	12,2 m	2 800 bar	9736E
Polyurethane	9,5 mm High Flow	6,1 m	2 800 bar	9782E	Rubber, Wire-braid	9,5 mm High Flow	15,3 m	2 800 bar	9779E
Polyurethane	9,5 mm High Flow	15,3 m	2 800 bar	9783E	Non-Conductive	6,4 mm	1,8 m	2 800 bar	9773
Rubber, Wire-brai	d 6,5 mm	0,9 m	2 800 bar	9755E	Non-Conductive	6,4 mm	3,1 m	2 800 bar	9774
Rubber, Wire-brai	d 6,5 mm	1,8 m	2 800 bar	9756E	Non-Conductive	6,4 mm	6,1 m	2 800 bar	9775
Rubber, Wire-brai	d 6,5 mm	1,8 m	2 800 bar	9754E [*]					

NOTE: Polyurethane hoses not recommended for use where heat or weld splatter conditions exist. *Furnished with 9798 hose half coupler and 9800 dust cap. Other lengths available on request





CYLINDER AND HOSE COUPLERS

Designed for use up to 700 bar with hydraulic jacks, cylinders, etc. They are the threaded union type for interchanging cylinders in seconds. Each half is valved disconnected. These couplers also permit the separation of cylinders or hose from pump when at 0 psi with minimal oil loss. No. 9795 - Complete quick coupler, 3/8" NPTF. (Includes two 9800 dust caps.) No. 9798 - Male (hose) half coupler (includes hose half dust cap), 3/8" NPTF. No. 9796 – Female (cylinder) half coupler with No. 9800 dust cap, 3/8" NPTF. No. 9796-V – Same as 9796, but with Viton coupler only. Wt., 0.1 kg. seals.

No. 9796-E - Same as 9796, but with EPR seals.

No. 9799 - Optional metal dust cap (hose half).

No. 9797 - Optional metal dust cap (cylinder half).

NO-SPILL. PUSH-TO-CONNECT HYDRAULIC HOSE COUPLERS

with a precision ball for a tight shutoff when with locking collar and flush face designed for high pressure applications. The flushface concept makes it easy to clean both coupler ends before connecting. Our unique push-to-connect, "dry-break" design eliminates oil spillage. The locking collar makes accidental disconnects a thing of the past. For 700 bar operation. Designed to permit high oil flow. No. 9792 - Female (cylinder) half quick No. 9793 - Male (hose) half guick coupler only. Wt., 0,1 kg. No. 9794 - Complete quick coupler (male and female). Dust caps not included. Wt.,0,2 kg.

Couplers

HYDRAULIC COUPLER DUST CAP

Dust cap fits either male or female half couplers.

No. 9800 – Dust cap. For male or female High flow, no-spill, push-to-connect couplers 3/8" NPTF half couplers. Wt., 0,1 kg.



Gauges

Analog & Digital

9042DG

ÍSPX.

Technical Attributes





Typical Mounting Setups



Digital hydraulic pressure gauge

cm2

- Digital gauge is easier to read and offers better accuracy¹ than a conventional analog gauge. ٠
- The laser welded stainless steel sensor & socket and the IP67 weatherproof rating make this product suitable . for use in even the most demanding of applications. Five pre-programmed engineering units allow technicians to read pressure in the unit of measure most applicable to the process.
- The gauge also features a bar graph display for enhance visibility. ٠
- Includes: automatic off (battery conservation), pressure tare, minimum pressure memory and maximum pressure. ٠
- Vibration & Shock tested to MIL-STD-202G.
- Agency Compliance/Approval: RoHS, CE, ASME B40.7, UL, cUL 61010-1 memory. ٠
- The gauges are calibrated for life at the factory. (They can be certified in the field if required). ٠

Gauge No.	Face Dia	Rated Pressure psi (bar)	Temp Range	Use with Cylinder Series	IP Rating	Batteries	Typical Battery Life	Accuracy	Product Weight
9042DG	2-1/2"	0-10,000 (0-700)	-4 °F to +140 °F (-20 °C to +60 °C)	All	IP67	2 x AA (LR6)	2,000 hrs	0.5% F.S.	0.53 lb 0.24 kg

Heavy-duty Hydraulic Pressure Gauges

- Gauges feature an easily readable and highly visible, red day-glo needle.
- High strength steel bourdon tube ensures high cycle life.
- Have ¹/₄" NPT connections.





(STANDARD PRESSU	IRE GAUGE ORDERING INF	ORMATION		
				Major	Minor	Silicone	Use With	Gauge
	Face Dia.	psi/Bar	Tons	Graduations	Graduations	Filled	Cylinder Series	No.
	63,5 mm	0-10,000 /.0-690	-	2000 psi, 100 Bar	200 psi, 20 Bar	Yes	All	9040E
	100 mm	0-10,000 /.0-690	-	1000 psi, 100 Bar	100 psi, 10 Bar	Yes	All	9052E
	100 mm	0-10,000 /.0-690	0-5	2000 psi, 1 Ton	200 psi, .1 Ton	Yes	C & RLS	9053E
	100 mm	0-10,000 /.0-690	0-10	2000 psi, 1 Ton	200 psi, .1 Ton	Yes	C, RD, RH, RLS & RSS	9055E
	100 mm	0-10.000 /0,0-690	0-15	2000 PSI, 1 Ton	200 PSI, 0,2 Ton	Yes	С	9057E
			0-17.5,		200 psi, .5 Ton on			
	100 mm	0-10,000 /.0-690	0-30 and	2000 psi, 5 Ton	30, 50 Ton Scales; .2	Yes	RT172, RT302, RT503	9059E
			0-50		Ton on 17.5 Ton Scale			
	100 mm	0-10.000 /0,0-690	0-20	2000 PSI, 5 Ton	200 PSI, 0,5 Ton	Yes	RH, RLS, RSS	9061E
	100 mm	0-10,000 /.0-690	0-25	2000 psi, 5 Ton	200 psi, .5 Ton	Yes	C & RD	9063E
	100 mm	0-10,000 /.0-690	0-30	2000 psi, 5 Ton	200 psi, .5 Ton	Yes	RH†, RLS & RSS	9065E
	100 mm	0-10,000 /.0-690	0-50	2000 psi, 5 Ton	200 psi, .5 Ton	Yes	RH†, RLS & RSS	9067E
	100 mm	0-10,000 /.0-690	0-55	2000 psi, 5 Ton	200 psi, .5 Ton	Yes	C, R, RA & RD	9069E
	100 mm	0-10,000 /.0-690	0-60	2000 psi, 5 Ton	200 psi, 1 Ton	Yes	RH	9071E
	100 mm	0-10,000 /.0-690	0-75	2000 psi, 5 Ton	200 psi, 1 Ton	Yes	C, RLS & RD8013	9073E
	100 mm	0-10,000 /.0-690	0-100	2000 psi, 10 Ton	200 psi, 1 Ton	Yes	C, R, RA, RD, RH,	9075E
							RLS†, RSS† & RT1004†	
	100 mm	0-10,000 /.0-690	0-150	2000 psi, Initial	200 psi, 2 Ton	Yes	C, R, RD & RLS	9077E
				10 Then 20 Ton				
	100 mm	0-10,000 /.0-690	0-200	2000 psi, 20 Ton	200 psi, 2 Ton	Yes	R, RD & RH†	9079E
				10 Then 20 Ton				
	150 mm	0-10,000 /.0-690	0-690	1000 psi, 100 Bar	100 psi, 10 Bar	No	All	9089

† The tonnage scale on the gauge is based on a different effective area. A slight error in tonnage reading will occur relative to the different effective area.

Gauges

Analog & Digital





Fluids **HYDRAULIC**

Standard, Flame Out[®], Biodegradable and Low Temp.

Oil Description	Qty.	Order No.
Standard Oil	0,91	9636
Standard Oil	3,8	9637
Standard Oil	9,5	9638
Standard Oil	2081	9616
Flame-Out®	3,8	9639
Flame-Out®	9,5 I	9640
Biodegradable	3,8	9645
Biodegradable	9,5 I	9646
Low Temp.	3,8	9647

HYDRAUE.IK Gil	

	2011/10	inp.	0,01	••••						
		Spec. Gravity			SPECIFICATIO	INS	Vis	cosity		Foam
Decorintion	Grade	at 16°C	Color (ASTM)	Flash	Fire	Pour	SUS @	SUS @ (00°C)	Viscosity	Test
Description	(ASTM)	(Ng / I)	(ASTM)	Pullit	PUIIIL	ruiiit	(30 0)	(33 0)	IIIUEX	(ASTM)
Standard Oil	215	0.88	2.0	204°C	221°C	-34°C	215	48	100	Pass
									min.	
Flame-Out°	220	0.91	Light Amber	260°C	288°C	-26°C	220	55	140	Pass
									min.	
Biodegradable	_	0.92	2.0	224°C	NA*	-30°C	183	53	213	Pass
									min.	
Low Temp.	_	0.87	6.5	180°C	204°C	-45°C	183	52	190	Pass
			(Red)						min.	

*Not available.

Standard Hydraulic Oil

- For dependable performance of all your hydraulic pumps and cylinders.
- Contains foam suppressant additives and has a high viscosity index. Flame-Out[®] 220 fire resistant
- hvdraulic fluid
- · Contains anti-rust, anti-foam and antisludge additives.
- Provides fire resistant protection.
- Provides maximum lubrication and heat transfer.
- range
- No need to change seals in your Power Team equipment. Just drain the standard oil and replace it with Flame-Out 220.

Biodegradable Hydraulic Fluid • Biodegradable, non-toxic fluid

- withstands moderate to severe operating conditions; provides excellent protection against rust. Offers superior anti-wear properties,
- has excellent multi-metal compatibility. Developed to meet stringent performance requirements and
- satisfy growing environmental needs for hydraulic fluids which are readily • Offers a wider operating temperature biodegradable and non-toxic. Can be used with all Power Team pumps, cylinders, valves and other accessories using standard seals. Depending on the or to order a MATERIAL SAFETY DATA contamination or degradation levels which might be present in used fluid, small amounts of this substance, if spilled, will not affect ground water or the environment. Acceptable methods of disposal include use as a fuel supplement. Since this fluid will not typically be hazardous waste, additional disposal options may be available,

(Note: Will burn if heat source is extreme enough. Will not, however, propagate the flame and is self-extinguishing when there is no ignition source.)

including land farming or processing through sewage treatment facilities, if necessary approvals are obtained from appropriate regulatory authorities. This fluid has been tested against EPA 560/6-82-003 and OECD 301 for biodegradability, and toxicity has been tested against EPA 560/ 6-82-002 and OECD 203: 1-12. Not recommended for operation in temperatures below -7 °C or above 71°C. Recommended storage temperatures not below -23°C or above 77°C For additional technical information

SHEET call 1-800-477-8326

Low–Temperature Oil

Provides smooth, reliable operation in the coldest climate conditions.



No. 9691 - "Y" Manifold

Extremely useful when connecting two hydraulic cylinders to a single line. Has No. 9627 - Manifold block three 3/8" NPTF ports. Wt. 0.45 kg.

No. 9634 - Manifold block

This manifold is for multiple-cylinder installations, has four 3/8" NPTF ports and two 1/4" mounting holes. Wt. 0,7 kg.

No. 9635 – Manifold block

This hex-shaped manifold offers extra versatility with six 3/8" NPTF ports and two 1/4" mounting holes. Wt. 0,9 kg.

No. 9617 – Manifold block

When a multiple-cylinder installation is required, this manifold is invaluable. Has six 3/8" NPTF ports to handle larger longer mounting screws are required. multiple-cylinder systems. Wt. 1.4 kg.

No. 9648 – Manifold block

This 178 mm long manifold block has

126

mounting holes. Wt. 2,7 kg. No. 9626 – Pump mounted manifold block

flow rate is 19 l/min. Note: If used on PE30 or PG30 series pump, 12,7mm

separately.

mounting holes. Wt.1,2 kg.

This 406,4 mm long manifold block allows you to mount the 9575 or 9596 valves without interference. Has seven 3/8" NPTF ports and two 6,4 mm

Converts pumps with pump mounted valves for use with remote mounted valves. This manifold block is subplate mounted on the pump cover plate and provides 3/8" NPTF pressure and return ports. Maximum recommended Order four (4) No. 11956 screws

seven 3/8" NPTF ports and two 6,4 mm 9642 AND 9644 MANIFOLD BLOCKS WITH NEEDLE VALVES

For independent multiple-cylinder operation, feature needle valves for precise manual control. Designed for remote-mounted applications. Can be used with all Power Team pumps. No. 9642 - Manifold with two needle valves for control of two cylinders. Has four 3/8" NPTF ports. Wt. 3,7 kg No. 9644 - Manifold with four needle valves for control of four cylinders. Has six 3/8" NPTF ports. Wt. 7,4 kg



Fi	ttings				9683	Male connector. 57 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.
70	0 bar				70 84	male ends. Wt. 0,1 kg
Po A	ower Team fitting Il applications.	gs:			9685	Coupling. 1/4" NPTF female and 3/8" NPTF female. Wt. 0.1 kg.
					9686	90° elbow. 3/8" NPTF female ends. Wt. 0.2 kg.
		9190	Hyd. tubing. 3/8" O.D. x .065" wall, 15,3 m. (10 pieces 1,53 m long.) Wt. 5,5 kg.		9687	Pipe plug. Heat-treated, 3/8" NPTF. Wt. 0.1 kg.
2		9670	Tee adapter. For installing gauge between pump and hose coupling. Has 1/4" and 3/8" NPTF female and 3/8" NPTF male		9688	Pipe plug. Heat-treated, 1/4" NPTF. Wt. 0.1 kg.
Lille'			ports. Wt. 0,2 kg.		9689	Connector. 1/4" NPTF male and 3/8" NPTF female. Wt. 0.1 kg.
うろう		9671	Double tee adapter. Permits use of more than one cylinder in series with one pump. Three 3/8" NPTF female ports. Wt. 0,5 kg.		9690	Male connector. 43 mm long, 1/4" NPTF male ends. Wt. 0.1 kg.
ינפר		9672	Service tee. Two 3/8" NPTF female internal, one 3/8" NPTF male external. Wt 0.3 kg		9692	Straight connector. 3/8" tube x 3/8" male NPTF. Wt. 0.1 kg.
Ð		9673*	Swivel connector. 3/8" NPSM male, 1/4"		9693	90° elbow. 3/8" tube x 3/8" male NPTF. Wt. 0.1 kg.
וייתרו		9674	Male connector. 43 mm long, 1/4" x 3/8"		9694	45° elbow. 3/8" tube x 1/4" male NPTF. Wt. 0.1kg.
ערת		9675*	Swivel connector. 3/8" NPTF male, 3/8"		9695	Tee. 3/8" tube. Wt. 0.1 kg.
3		00704	NPSM temale. Wt. 0,1 kg.		9696	Male run tee. 3/8" tube x 1/4" male NPTF. Wt. 0.1 kg.
		9676*	NPSM female. Wt. 0,1 kg.		9697	Male branch tee. 3/8" tube x 1/4" male NPTF. Wt. 0.1 kg.
		9677*	45° swivel connector. 3/8" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.		0608	Cross 3/8" tube Wt 0.2 kg
		9678	45° fitting. Used when mounting gauge at an angle on connection such as 9670. Male and female 1/4" NPTF ends. Wt. 0,1 kg.		3038	
		9679	Connector. 1/4" NPTF female and 3/8" NPTF male. Wt. 0.1 kg.		9699	45° gauge fitting, 3/8" NPTF male and female, and 1/4" NPTF female at $45^\circ.$ Wt. 0.3 kg.
		9680	Coupling. Both ends 3/8" NPTF female. Wt. 0.1 kg.		9705	Fitting, swivel. 3/8" NPTF male to 3/8" NPTF female. 90° fitting with internal 370 micron screen. May be rotated 360° about
		9681	Street elbow. Male and female 3/8" NPTF ends. Wt. 0,1 kg.			male thread axis.
		9682	Male connector. 43 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.	NOTE: Power Team hydraulic hydraulic products and are s bar unless otherwise noted.	: fittings a uitable fo	re intended for use with our high pressur r use at max. working pressures of 700

* CAUTION: On part numbers 9673, 9675, 9676 and 9677 the female swivel end of these adapters is a straight pipe thread (NPSM) with a 30° seat. All male pipe fittings that are used with these female swivel adapters must have an internal 30° seat in order to effect a proper seal. All Power Team male fittings are manufactured with a 30° seat except 9687 and 9688.

Remote Mounted Valves

Order No.	Page No.	*Cylinder Application	Operation	Valve Type	Volt	Advance/ Return	Advance/ Hold Return	Posi- Check* Feature
508	131	S.A & D.A.	Manual	4-way, 3 Pos. Closed Center	_	no	yes	yes
509	131	S.A. & D.A.	Manual	4-way, 3 Pos. Tandem Center	_	no	yes	yes
9514	131	D.A.	Solenoid	4-way, 3 Pos. Tandem Center	115	no	yes	yes
)524	130	S.A. & D.A.	Solenoid	3/4-way, 2 Pos.	230	no	yes	no
9525	131	D.A.	Solenoid	4-way, 3 Pos. Tandem Center	230	no	yes	yes
9526	131	S.A.	Solenoid	3-way, 2 Pos.	230	no	yes	no
554	130	S.A. & D.A.	Solenoid	3/4-way, 2 Pos.	24	no	yes	no
555	131	D.A.	Solenoid	4-way, 3 Pos. Tandem Center	24	no	yes	yes
556	131	S.A.	Solenoid	3-way, 2 Pos.	24	no	yes	no
559	131	S.A.	Solenoid	3-way, 2 Pos.	115	no	yes	no
593	130	S.A. & D.A.	Solenoid	3/4-way, 2 Pos.	115	no	yes	no
595	130	S.A. & D.A.	Air	3/4-way, 2 Pos.	_	no	yes	no
		In-Lin-	e Valves					

In-Line Valves

Order No.	Page No.	*Cylinder Application	Operation	Valve Type	Volt	Advance/ Return	Advance/ Hold Return	Posi-Check* Feature
9575	132	S.A.	Manual	Shut-Off Valve	_	_	_	_
9580	133	S.A.	Automatic	One-way Check Valve	_	-	_	_
9581	133	S.A. & D.A.	Automatic	Pilot Op. Check Valve	_	_		_
9596	132	S.A.	Manual	Load Lowering Valve	_	_	_	_
9597	132	S.A. & D.A.	Automatic	Sequence Valve	_	-		_
9608	132	S.A. & D.A.	Automatic	Pressure Reducing Valve	_	_		
9623	133	S.A. & D.A.	Automatic	Pressure Relief Valve	_	-	_	_
9631	133	S.A. & D.A.	Automatic	Metering Valve		_		
9633	133	S.A. & D.A.	Automatic	Pressure Regulator Valve	_	_		
9720	132	S.A. & D.A.	Automatic	Counter Balance Valve	_	special	_	_
9721	132	S.A. & D.A.	Automatic	Counter Balance Valve	_	special	_	_
RV21278	133	-	Automatic	Relief Valve	_	_	_	_

"S.A." represents single-acting cylinders, "D.A." represents double-acting cylinders. For pump-mounted valves, see pages 51-57.

Valves HYDRAULIC REMOTE/IN-LINE

Valve selection chart



Valves **HYDRAULIC REMOTE MOUNTED**

700 bar. 1/4" ports 191/min max flow

3/4-way/2-position solenoid and air actuated valves

Application: Single- or double-acting cylinders.

Actuation: 9593, 9524 and 9554 are solenoid operated, 9595 is air operated. Operation with single-acting cylinder: Either oil port "A" or "B" must be plugged on valve. With port "B" plugged, solenoid is energized to position "A," oil port "A" becomes pressurized. When solenoid is energized to position "B," oil port "A" becomes the return port.

Operation with multiple single-acting cvlinders: A pressure line from one bank can be connected to oil port "A" and the other to oil port "B" on the valve. Sequence: When energized to position "A," oil port "A" becomes pressurized and clamps the fixture connected to oil port "A"; oil port "B" becomes a "return" port for cylinder connected to oil port "B," and retracts it. The opposite happens when solenoid "B" is energized.





Operation with double-acting cylinder: Port No. 9593 - 3/4-way/2-position, remote mounted solenoid valve, 115 volt, 50/60

"A" is connected to "advance" port of cylinder, oil port "B" connects to cylinder "return" port. Solenoid is energized to position "A," oil port "A" becomes pressurized to extend cylinder piston. The opposite happens when solenoid "B" is energized. Valve does not hold in "retract" No. 9595 - Same as 9593 except is air position.

NOTE: When using more than one valve on required). Wt.,5,2 kg. a pump, the tank port may require a check **NOTE:** Valves above are shipped without valve to permit inadvertent, momentary extension of a retracted cylinder. control (see page 106). The 9595 can be

NOTE: If pump is equipped with an internal outlet check, a "hold" position can be maintained with the pump shut off.

NOTE: Valves have 1/4" NPTF ports. 3/8" to 1/4" adapters are included.

Port E

Hz. Wt., 7 kg.

230 volt, 50/60 Hz.

volt, 50/60 Hz.

(see page 106).

Port

50.8 mm

¥ |⊕

No. 9524 - Same as 9593 except with

No. 9554 - Same as 9593 except with 24

operated (minimum of 3,5 bar air pressure

controls. The 9524, 9554 and 9593 can

be used with the 304718 remote hand

used with the 209593 remote hand control

___79.4 mr

Four Mtg. Holes for

¹/₄" Cap Screws.

NOTE: Maximum tank line pressure for remote mounted valves is 35 bar.







Pressure Port

1. To actuate one single-acting cylinder. 2. To actuate two single-acting cylinders. 3. To actuate one double-acting cylinder.

NOTE: Valves above are shipped without control switch. Use 202777 remote hand switch (see page 116).

A CAUTION: To prevent sudden, uncontrolled descent of a load as it is being lowered, use a No. 9596 Load Lowering Valve or No. 9720 Counter Balance Valve (see page 132) in conjunction with the directional valve used in your application.



4-way/3-position (closed center) and (tandem center) manual valves with Posi-Check' Application: Single- or double-acting cylinder. When used with single-acting cylinders, one port must be plugged. For doubleacting cylinders, either port can be used for

"advance" or "return." Actuation: Lever-operated, detent positioned.

Functions: The 9508 provides "advance," "hold" and "return" positions with all ports blocked (closed center) in the "hold" position. IMPORTANT: A 9580 in-line check valve (see The 9509 has "advance," "hold" and "return" with tandem center (cylinder ports are blocked, pump remains running). Both valves have "Posi-Check" feature to guard against pressure loss when shifting from "advance"

to "hold."

No. 9508 – 4-way/3-position (closed center) manual valve, including subplate for remote mounting, Wt., 2.9 kg.

No. 9509 - Same as 9508, except is tandem center.

No. 9556 - Same as 9559 except for 24 volt, 50/60 Hz. **NOTE:** Valves above are shipped without control switch. Use 202777 remote hand switch (see page 106)

solenoid de-energized.

an outlet check valve.

230 volt. 50/60 Hz.

reservoir

A CAUTION: To prevent sudden, uncontrolled descent of a load as it is being lowered, use a No. 9596 Load Lowering Valve or No. 9720 Counter Balance Valve (see page 132) in conjunction with the directional valve used in your application. A CAUTION: The Posi-Check' feature will not hold the load when shifted directly A to B-B to A or from hold to A or B.

NOTE: Maximum tank line pressure for remote mounted valves is 35 bar.



9559

9526

9556

Port

3-WAY/2-POSITION SOLENOID VALVE Application: Single-acting cylinders. Actuation: Solenoid operated, 115 volt.

Function: Advances cylinder piston when solenoid is de-energized, and pump is running. When solenoid is energized, oil is directed back through valve "return" port and cylinder piston returns. To place cylinder in "hold" position, pump must be stopped or its flow held at the valve "pressure" port with the

NOTE: Valve is equipped with a 9631 snubber valve in port "A." The line from the "return" port of the valve must be unrestricted (7 bar back pressure maximum) back to the

No. 9559 - 3-way/2-position solenoid valve, 115 volt 50/60 Hz. Includes a remote mounting subplate. Wt., 4.4 kg. No. 9526 - Same as 9559 except for

Valves HYDRAULIC REMOTE MOUNTED

700 bar. 3/8" ports 191/min max flow



4-way/3-position (tandem center) solenoid valve with Posi-CHeck*

page 123) must be installed in the "pressure" Application: Double-acting cylinders. port if the supply pump is not equipped with Actuation: Solenoid operated, 115 volt, 50/60 Hz

> Functions: Push button control of "advance." "hold" and "return." The "Posi-Check" feature guards against pressure loss when shifting from "advance" to "hold." With valve in "hold" position, cylinder ports are blocked and oil is directed from pump to reservoir. NOTE: Do not allow return tank pressure to

exceed 35 bar at the valve. No. 9514 - 4-way/3-position (tandem center)

solenoid valve, 115 volt, 50/60 Hz. Remote hand control included. Wt., 4.6 kg. No. 9525 - Same as 9514 except for 230

volt. 50/60 Hz. No. 9555 - Same as 9514 except for 24 volt, 50/60 Hz.

NOTE: Consult factory before installing a pressure switch on any of these valves.



Valves **HYDRAULIC IN-LINE**

9597

Port P

Pressure

3%" NPTF

9608

Port B

Secondary

3/8" NPTF

700 bar. 191/min max flow rate

Port A

Primary

3%" NPT

Adjusting Screw

CAUTION: Over Pressure control must be set at a higher value



Double-

LOAD LOWERING VALVE

Application: Precision metering for controlled cylinder piston return.

Operation: Permits free flow when extending cylinder, built-in pressure relief and "Posi-Check®" locks and holds load in raised

position until operator opens valve. May be pre-set to provide consistent metered return, or operator may select rate of return with each actuation. Has 3/8" NPTF ports.

NOTE: Pressure relief valve setting is 830 bar. Operating pressure is 700 bar and max. flow rate is 19 I /min.

No. 9596 - Load lowering valve. Wt., 1 kg.

SEQUENCE VALVE

Application: Used when one cylinder in a multi-cylinder application must advance before any other.

Operation: Pump is connected to port "P" and separate cylinders to ports "A" and "B". When pressure is applied to port "P", cylinder "A" advances. Cylinder "B" will not advance until a predetermined pressure setting is reached in cylinder "A". Pressure setting is adjustable from 35 to 550 bar with adjustment screw; factory preset at 70 bar. Has 3/8" NPTF ports.

No. 9597 - Pressure control sequencing valve. Wt., 2,5 kg.

PRESSURE REDUCING VALVE

Application: Provides complete, independent pressure control to two or more clamping systems operated by a single power source

- **Operation:** Can be used to provide different pressures in various stages of a single system. Virtually zero leakage across valve means each system can be operated by a single continuous pressure source. Adjustable from 70 to 350 bar at outlet port "B" (secondary) Has 1/4" NPTF ports.
- No. 9608 Pressure reducing valve. Wt., 2,6 kg.



A CAUTION: The 9720 patented counter balance valve has a pilot pressure as high as 210 bar. Because this pressure is applied to the rod end of the cylinder while it is already under load, the system should not be sized for loads greater than 80% of cylinder rated capacity.

A CAUTION: To prevent sudden, uncontrolled descent of a load as it is being lowered, use a No. 9596 Load Lowering Valve or No. 9720 Counter Balance Valve in conjunction with the directional valve used in your application. See above, this page.

Shut-off valve

Application: This needle valve permits fine metering of hydraulic oil. Operation: Can be used for controlling multiple single-acting cylinders. No. 9575 - Shut off valve with 3/8" NPTF ports. Wt., 0,6 kg.

Check valve

Application: Permits flow of hydraulic oil in one direction only. Operation: Installs right in hydraulic line. No. 9580 - Check valve with 3/8" NPTF male ends. Wt., 0,2 kg.

Pilot operated check valve

Application: For use with open or tandem center valves. Permits free flow of fluid in one direction. **Operation:** Flow is blocked in opposite direction until pilot oil pressure is applied. This prevents the loss of pressure if the valve is inadvertently shifted or the pump line is broken. Minimum cracking

pressure is 4,1 bar. Required pilot pressure is approximately 16% of checked system pressure. No. 9581 - Pilot operated check valve with 3/8" NPTF ports. Wt., 1,7 kg.

"In-line" pressure relief valve

Application: Single- or double-acting cylinders. For remote locations in a hydraulic circuit where maximum pressure requirements are less than basic overload valve setting in pump. Operation: Adjustable from 70 to 700 bar. Valve is spring-loaded and direct-acting. No. 9623 - Pressure relief valve with 3/8" NPTF ports. Wt., 0,9 kg.

Metering valve

Application: For systems using large cylinders or extended lengths of hydraulic hose. Operation: Controls surges by restricting flow if it exceeds 26,5 I / min. When flow subsides, valve reopens automatically. Has 3/8" NPTF male end to thread into return port of system control valve,

and a 3/8" NPTF female end, permitting return hose to be directly connected.

No. 9631 - Metering valve. Wt., 0.1 kg.

"In-line" pressure regulator valve

Application: Single- or double-acting cylinders. Permits adjusting operating pressures at various values below relief valve setting of pump.

Operation: Regulator valve is easily adjusted to maintain pressures between 20 and 700 bar. Maintains a given pressure setting within 3% over repeated cycles. Flow range is 0,3 I/ min to 23 I / min.

No. 9633 - In-line pressure regulator valve with two 3/8" NPTF inlet ports, one 1/8" NPTF tank port and 1 m drain line kit. Wt., 0,9 kg.

Simply turn the handle clockwise to increase the pressure setting, counter-clockwise to reduce pressure. Note: 1 m Drain Line Kit is included.



NOTE: Care should be exercised to protect workers from hot, pressurized hydraulic oil. Install these valves only in an enclosed or shielded area.



Valve	Pressure	Valve	Pressure
Order No.	Setting (bar)	Order No.	Setting (bar
RV21278	697/738	RV21278-52	366/407
RV21278-6	41/44	RV21278-55	386/428
RV21278-10	62/69	RV21278-57	400/442
RV21278-15	103/117	RV21278-60	421/462
RV21278-20	131/152	RV21278-65	455/497
RV21278-28	186/207	RV21278-70	490/531
RV21278-30	207/235	RV21278-75	524/566
RV21278-32	214/228	RV21278-80	559/600
RV21278-35	241/262	RV21278-83	580/621
RV21278-40	283/310	RV21278-86	600/642
RV21278-43	304/331	RV21278-88	614/662
RV21278-48	338/366	RV21278-90	628/669
RV21278-50	352/393	Preset – Non-Se	erviceable

www.powerteam.com