

Low Profile BOTTLE JACKS

12, 20 & 30 Ton

The right choice for those lower clearance jobs.

((

- All the quality, features and lifting capacity of the standard jacks in short form. The 12-ton and 20-ton models feature screw extensions for added versatility.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.
- All jacks operate both vertically and horizontally for use in a variety of lifting, pushing and spreading applications.

ORDERING INFORMATION													
Product			Retracted Height	Length of Screw	Height w/Screw	No. Pump Strokes to	Saddle		Pump Handle	Handle Effort at		Metric tons	
Cap.	Stroke	Order	Min.	Ext.	Ext.	Ext. Piston	Dia.	Base Size	Length	Rated Cap.	Carry	at 700	Weight
Tons	(mm)	Number	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)	Handle	bar	(kg)
12	95	9012A	171	76	343	26	48	165x106	605	27	Yes	10,9	6,4
20	86	9020A	181	40	305	22	51	183x129	800	32	Yes	18,1	10,1
30	79	9130A	181		260	35	60	192x141	1.000	23	Yes	27,2	13,7
‡ 2 Spe	ed: Rapid	d advance≈	40 strokes;	Lift mode≈1	60 stroke								